

## Luminaire

Code 1053010A  
Name CASTORE SOSPENSIONE 250

## Measurerm.

Code FTS0002069-B  
Name CASTORE SOSPENSIONE 250

Luminaire Flux	1227 lm	Luminaire Power	12.0 W	Efficacy	102.249 lm/W	Efficiency	80.67%
Source Flux	1521 lm	Maximum value	72.60 cd/klm	Position	C=0.00 G=55.00	CG	Rotosymmetrical
Round Luminaire		Diam.	250 mm	Height	250 mm		
Round Luminous Area		Diam.	250 mm	Height	250 mm		
Horizontal Luminous Area		0.049087 m <sup>2</sup>		Emitting area on Plane 180°		0.062500 m <sup>2</sup>	
Emitting area on Plane 0°		0.062500 m <sup>2</sup>		Emitting area on Plane 270°		0.062500 m <sup>2</sup>	
Emitting area on Plane 90°		0.062500 m <sup>2</sup>		Glare area at 76°		0.072519 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		27-08-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1521 lm	


Lamping=LED DIM 1x12W (E27) CCT=2700K CRI=80

C.I.E. 25 50 76 56 81  
F UTE 0.45 J + 0.36 T

D DIN 5040  
B NBN

C11  
BZ 8

Diam=250mm



Semipiani C

180.0 ——— 0.0

ULOR 35.52 %

DLOR 45.15 %

RN 44.03 %

