

Luminaire

Code 0116010A
Name DIOSCURI PAR/SOFF 350

Measurerm.

Code FTS0002522
Name DIOSCURI PAR/SOFF 350

Luminaire Flux	2186 lm	Luminaire Power	21.0 W	Efficacy	104.072 lm/W	Efficiency	89.13%
Source Flux	2452 lm	Maximum value	76.32 cd/klm	Position	C=0.00 G=15.00	CG	Rotosymmetrical
Round Luminaire		Diam.	350 mm	Height	350 mm		
Round Luminous Area		Diam.	350 mm	Height	350 mm		
Horizontal Luminous Area		0.096211 m ²		Emitting area on Plane 180°		0.122500 m ²	
Emitting area on Plane 0°		0.122500 m ²		Emitting area on Plane 270°		0.122500 m ²	
Emitting area on Plane 90°		0.122500 m ²		Glare area at 76°		0.142137 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2452 lm	

Lamping=LED DIM 1x21W (E27) CCT=2700K CRI=80

C.I.E. 25 50 75 53 89
F UTE 0.48 J + 0.42 T

D DIN 5040
B NBN

C11
BZ 8

Diam=350mm



Semipiani C

180.0 ——— 0.0

ULOR 41.57 %

DLOR 47.56 %

RN 46.64 %

