

## Luminaire


Code 0117010A  
Name DIOSCURI PAR/SOFF 420

## Measurerm.

Code FTS0002523  
Name DIOSCURI PAR/SOFF 420

Luminaire Flux	2186 lm	Luminaire Power	21.0 W	Efficacy	104.072 lm/W	Efficiency	89.13%
Source Flux	2452 lm	Maximum value	76.32 cd/klm	Position	C=0.00 G=15.00	CG	Rotosymmetrical
Round Luminaire		Diam.	420 mm	Height	420 mm		
Round Luminous Area		Diam.	420 mm	Height	420 mm		
Horizontal Luminous Area		0.138544 m <sup>2</sup>		Emitting area on Plane 180°		0.176400 m <sup>2</sup>	
Emitting area on Plane 0°		0.176400 m <sup>2</sup>		Emitting area on Plane 270°		0.176400 m <sup>2</sup>	
Emitting area on Plane 90°		0.176400 m <sup>2</sup>		Glare area at 76°		0.204677 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2452 lm	
Lamping=LED DIM 1x21W (E27) CCT=2700K CRI=80							
C.I.E.	25 50 75 53 89			D DIN 5040		C11	
F UTE	0.48 J + 0.42 T			B NBN		BZ 8	

Diam=420mm



Semipiani C

180.0 ——— 0.0

ULOR 41.57 %

DLOR 47.56 %

RN 46.64 %

