


Luminaire

Code 0761W10A+0780010A
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA DIFF.PERG.320- 2700K

Measurem.

Code FTS1701372
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA DIFF.PERG.320- 2700K

Luminaire Flux	1867.91 lm	Luminaire Power	31.00 W	Efficacy	60.26 lm/W	Efficiency	100.00%
Lamps Flux	1867.91 lm	Maximum value	436.82 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	320 mm 320 mm	Height Height	220 mm 220 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.080425 m2 0.070400 m2 0.070400 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.070400 m2 0.070400 m2 0.087765 m2	
Coordinate system Date Measurement Distance		CG 21-09-2016 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1867.91 lm	
LED Flux=2722,9lm LED Power=25,6W Eff=69% EfcLed=106lm/W EfcLum=60lm/W Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E. F UTE	67 86 94 84 100 0.84 C + 0.16 T			D DIN 5040 B NBN		B51 BZ 2 / 0.6 / BZ 3 / 4 / BZ 4	



Luminaire

Code 0761W10A+0780010A
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA DIFF.PERG.320- 2700K

Measurerm.

Code FTS1701372
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA DIFF.PERG.320- 2700K

Luminaire Flux	1867.91 lm	Luminaire Power	31.00 W	Efficacy	60.26 lm/W	Efficiency	100.00%
Lamps Flux	1867.91 lm	Maximum value	436.82 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	320 mm	Height	220 mm		
Round Luminous Area		Diam.	320 mm	Height	220 mm		
Horizontal Luminous Area		0.080425 m2		Emitting area on Plane 180°		0.070400 m2	
Emitting area on Plane 0°		0.070400 m2		Emitting area on Plane 270°		0.070400 m2	
Emitting area on Plane 90°		0.070400 m2		Glare area at 76°		0.087765 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-09-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1867.91 lm	


LED Flux=2722,9lm LED Power=25,6W Eff=69% EfcLed=106lm/W EfcLum=60lm/W Ra=90 SDCM=2 L70(6K)=50000h

C.I.E.	67 86 94 84 100	D DIN 5040	B51
F UTE	0.84 C + 0.16 T	B NBN	BZ 2 / 0.6 / BZ 3 / 4 / BZ 4

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.94	1.87	2.81	3.74	4.68	OC	0.94	1.87	2.81	3.74	4.68
OB	0.94	1.87	2.81	3.74	4.68	OD	0.94	1.87	2.81	3.74	4.68

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	815.94	808.61	762.38	706.40	628.31	278.50	116.55	92.60	69.28	53.75
OB	815.94	808.61	762.38	706.40	628.31	278.50	116.55	92.60	69.28	53.75
OC	815.94	808.61	762.38	706.40	628.31	278.50	116.55	92.60	69.28	53.75
OD	815.94	808.61	762.38	706.40	628.31	278.50	116.55	92.60	69.28	53.75



H[m]	D[m]	Max lux	Med lux	Alpha=43.1°+43.1°	G=0.0
1.00	1.87	816	333		
2.00	3.74	204	83		
3.00	5.62	91	37		
4.00	7.49	51	21		
5.00	9.36	33	13		