

## Luminaire

Code 0761W30A+0772020A  
 Name TOLOMEO MEGA LED BODY BLACK/DIMM + TOLOMEO MEGA TESSUTO NRO 360- 2700K

## Measurem.

Code FTS1701400  
 Name TOLOMEO MEGA LED BODY BLACK/DIMM + TOLOMEO MEGA TESSUTO NRO 360- 2700K

Luminaire Flux	1570.76 lm	Luminaire Power	31.00 W	Efficacy	50.67 lm/W	Efficiency	100.00%
Sources Flux	1570.76 lm	Maximum value	487.71 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	360 mm	Height	250 mm		
Round Luminous Area		Diam.	360 mm	Height	0 mm		
Horizontal Luminous Area			0.101788 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.024625 m2
Coordinate system		CG		Symmetry Type			Rotosymmetrical
Date		21-09-2016		Maximum Gamma Angle			180
Measurement Distance		0.00		Measurement Flux			1570.76 lm


LED Flux=2722,9lm LED Power=25,6W Eff=58% EfcLed=106lm/W EfcLum=51lm/W Ra=90 SDCM=2 L70(6K)=50000h

C.I.E. 72 91 98 93 100  
 F UTE 0.93 B + 0.07 T

D DIN 5040  
 B NBN

A61  
 BZ 2

Diam=360mm




Semipiani C

180.0 ——— 0.0

ULOR 6.67 %

DLOR 93.33 %

RN 6.67 %



## Luminaire

Code 0761W30A+0772020A  
 Name TOLOMEO MEGA LED BODY BLACK/DIMM + TOLOMEO MEGA TESSUTO NRO 360- 2700K

## Measurement

Code FTS1701400  
 Name TOLOMEO MEGA LED BODY BLACK/DIMM + TOLOMEO MEGA TESSUTO NRO 360- 2700K

Luminaire Flux	1570.76 lm	Luminaire Power	31.00 W	Efficacy	50.67 lm/W	Efficiency	100.00%
Sources Flux	1570.76 lm	Maximum value	487.71 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	360 mm	Height	250 mm		
Round Luminous Area		Diam.	360 mm	Height	0 mm		
Horizontal Luminous Area		0.101788 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.024625 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-09-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1570.76 lm	


LED Flux=2722,9lm LED Power=25,6W Eff=58% EfcLed=106lm/W EfcLum=51lm/W Ra=90 SDCM=2 L70(6K)=50000h

C.I.E.	72 91 98 93 100	D DIN 5040	A61
F UTE	0.93 B + 0.07 T	B NBN	BZ 2

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.90	1.80	2.71	3.61	4.51	OC	0.90	1.80	2.71	3.61	4.51
OB	0.90	1.80	2.71	3.61	4.51	OD	0.90	1.80	2.71	3.61	4.51

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	766.08	763.49	758.93	716.94	643.24	201.00	131.19	83.89	40.89	10.02
OB	766.08	763.49	758.93	716.94	643.24	201.00	131.19	83.89	40.89	10.02
OC	766.08	763.49	758.93	716.94	643.24	201.00	131.19	83.89	40.89	10.02
OD	766.08	763.49	758.93	716.94	643.24	201.00	131.19	83.89	40.89	10.02



H[m]	D[m]	Max lux	Med lux	Alpha=42.1°+42.1°	G=0.0
1.00	1.80	766	345		
2.00	3.61	192	86		
3.00	5.41	85	38		
4.00	7.22	48	22		
5.00	9.02	31	14		