

Luminaire

Code 1200000A
Name Alphabet of light - 0

Measurerm.

Code FTS1700214-A
Name Alphabet of light - 0

| | | | | | | | |
|----------------------------|---------|-------------------------|---------------|-----------------------------|-----------------|-------------------------|--------------------|
| Luminaire Flux | 2808 lm | Luminaire Power | 32.0 W | Efficacy | 87.756 lm/W | Efficiency | 100.00% |
| Source Flux | 2808 lm | Maximum value | 114.12 cd/klm | Position | C=90.00 G=89.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 50 mm | Width | 650 mm | Height | 950 mm |
| Rectangular Luminous Area | | Length | 50 mm | Width | 650 mm | Height | 949 mm |
| Horizontal Luminous Area | | 0.032500 m ² | | Emitting area on Plane 180° | | 0.047500 m ² | |
| Emitting area on Plane 0° | | 0.047500 m ² | | Emitting area on Plane 270° | | 0.617500 m ² | |
| Emitting area on Plane 90° | | 0.617500 m ² | | Glare area at 76° | | 0.053952 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 10-03-2022 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 2808 lm | |


LED Flux=3201lm LED Power=32W Eff=88% EfcLed=100lm/W EfcLum=88lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h

C.I.E. 21 46 73 50 100
F UTE 0.50 J + 0.50 T

D DIN 5040
B NBN

C11
BZ 9

50mm x 650mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %

