

## Luminaire


Code 1201H00A  
Name Alphabet of light - H

## Measurment

Code FTS1700195-A  
Name Alphabet of light - H

Luminaire Flux	2664 lm	Luminaire Power	32.0 W	Efficacy	83.256 lm/W	Efficiency	100.00%
Source Flux	2664 lm	Maximum value	114.12 cd/klm	Position	C=90.00 G=89.00	CG	Double Symmetrical
Rectangular Luminaire		Length	50 mm	Width	650 mm	Height	950 mm
Rectangular Luminous Area		Length	50 mm	Width	650 mm	Height	949 mm
Horizontal Luminous Area		0.032500 m2		Emitting area on Plane 180°		0.047500 m2	
Emitting area on Plane 0°		0.047500 m2		Emitting area on Plane 270°		0.617500 m2	
Emitting area on Plane 90°		0.617500 m2		Glare area at 76°		0.053952 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		10-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2664 lm	
LED Flux=3037lm LED Power=32W Eff=88% EfcLed=95lm/W EfcLum=83lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h							
C.I.E.	21 46 73 50 100			D DIN 5040		C11	
F UTE	0.50 J + 0.50 T			B NBN		BZ 9	

50mm x 650mm



Semipiani C

180.0 ——— 0.0  
270.0 ——— 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %

