


Luminaire

Code 1201R00A
 Name Alphabet of light - R
Measurem.
 Code FTS1700205-A
 Name Alphabet of light - R

| | | | | | | | |
|---|-----------------|-------------------------|---------------|-----------------------------|-----------------|-------------------------|--------------------|
| Luminaire Flux | 3060 lm | Luminaire Power | 36.0 W | Efficacy | 85.006 lm/W | Efficiency | 100.00% |
| Source Flux | 3060 lm | Maximum value | 114.12 cd/klm | Position | C=90.00 G=89.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 50 mm | Width | 650 mm | Height | 950 mm |
| Rectangular Luminous Area | | Length | 50 mm | Width | 650 mm | Height | 949 mm |
| Horizontal Luminous Area | | 0.032500 m ² | | Emitting area on Plane 180° | | 0.047500 m ² | |
| Emitting area on Plane 0° | | 0.047500 m ² | | Emitting area on Plane 270° | | 0.617500 m ² | |
| Emitting area on Plane 90° | | 0.617500 m ² | | Glare area at 76° | | 0.053952 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 10-03-2022 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 3060 lm | |
| LED Flux=3488lm LED Power=36W Eff=88% EfcLed=97lm/W EfcLum=85lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h | | | | | | | |
| C.I.E. | 21 46 73 50 100 | | | D DIN 5040 | | C11 | |
| F UTE | 0.50 J + 0.50 T | | | B NBN | | BZ 9 | |

50mm x 650mm



Semipiani C

180.0 ——— 0.0
 270.0 ——— 90.0

ULOR 50.00 %
 DLOR 50.00 %
 RN 50.00 %

