

Luminaire

Code 1202r00A
Name Alphabet of light - r

Measurem.

Code FTS1700179-A
Name Alphabet of light - r

Luminaire Flux	1233 lm	Luminaire Power	14.0 W	Efficacy	88.078 lm/W	Efficiency	100.00%
Source Flux	1233 lm	Maximum value	114.12 cd/klm	Position	C=90.00 G=89.00	CG	Double Symmetrical
Rectangular Luminaire		Length	50 mm	Width	350 mm	Height	650 mm
Rectangular Luminous Area		Length	50 mm	Width	350 mm	Height	650 mm
Horizontal Luminous Area		0.017500 m ²		Emitting area on Plane 180°		0.032500 m ²	
Emitting area on Plane 0°		0.032500 m ²		Emitting area on Plane 270°		0.227500 m ²	
Emitting area on Plane 90°		0.227500 m ²		Glare area at 76°		0.035768 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		10-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1233 lm	


LED Flux=1406lm LED Power=14W Eff=88% EfcLed=100lm/W EfcLum=88lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h

C.I.E. 21 46 73 50 100
F UTE 0.50 J + 0.50 T

D DIN 5040
B NBN

C11
BZ 9

50mm x 350mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 50.00 %

DLOR 50.00 %

RN 50.00 %

