

## Luminaire

Code 1202v00A  
Name Alphabet of light - v

## Measurum.

Code FTS1700183-A  
Name Alphabet of light - v

Luminaire Flux	1746 lm	Luminaire Power	20.0 W	Efficacy	87.306 lm/W	Efficiency	100.00%
Source Flux	1746 lm	Maximum value	114.12 cd/klm	Position	C=90.00 G=89.00	CG	Double Symmetrical
Rectangular Luminaire		Length	50 mm	Width	650 mm	Height	650 mm
Rectangular Luminous Area		Length	50 mm	Width	650 mm	Height	649 mm
Horizontal Luminous Area		0.032500 m <sup>2</sup>		Emitting area on Plane 180°		0.032500 m <sup>2</sup>	
Emitting area on Plane 0°		0.032500 m <sup>2</sup>		Emitting area on Plane 270°		0.422500 m <sup>2</sup>	
Emitting area on Plane 90°		0.422500 m <sup>2</sup>		Glare area at 76°		0.039397 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		10-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1746 lm	


LED Flux=1990lm LED Power=20W Eff=88% EfcLed=100lm/W EfcLum=87lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=36000h

C.I.E. 21 46 73 50 100  
F UTE 0.50 J + 0.50 T

D DIN 5040  
B NBN

C11  
BZ 9

50mm x 650mm



Semipiani C

180.0 ——— 0.0  
270.0 ——— 90.0

ULOR 50.00 %  
DLOR 50.00 %  
RN 50.00 %

