

## Luminaire


Code 1205000A  
Name ALPHABET OF LIGHT S LINEARE 180

## Measurement

Code FTS1701419-A  
Name ALPHABET OF LIGHT S LINEARE 180

Luminaire Flux	5226 lm	Luminaire Power	39.0 W	Efficacy	134.000 lm/W	Efficiency	100.00%
Source Flux	5226 lm	Maximum value	158.36 cd/klm	Position	C=45.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.090000 m <sup>2</sup>		Emitting area on Plane 180°		0.090000 m <sup>2</sup>	
Emitting area on Plane 0°		0.090000 m <sup>2</sup>		Emitting area on Plane 270°		0.002500 m <sup>2</sup>	
Emitting area on Plane 90°		0.002500 m <sup>2</sup>		Glare area at 76°		0.109100 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		24-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5226 lm	
LED Flux=6451lm LED Power=35W Eff=81% EfcLed=184lm/W EfcLum=134lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h							
C.I.E.	33 60 83 69 100			D DIN 5040	B21		
F UTE	0.69 H + 0.31 T			B NBN	BZ 6		

1800mm x 50mm



Semipiani C

180.0 ——— 0.0  
270.0 ——— 90.0

ULOR 30.60 %  
DLOR 69.40 %  
RN 30.60 %

