

## Luminaire


Code 1215L00A  
Name AOL MINI W L UPPERCASE

## Measurerm.

Code FTS2400018  
Name AOL MINI W L UPPERCASE

Luminaire Flux	616 lm	Luminaire Power	6.0 W	Efficacy	102.667 lm/W	Efficiency	100.00%
Source Flux	616 lm	Maximum value	186.86 cd/klm	Position	C=65.00 G=2.00	CG	Asymmetrical
Rectangular Luminaire		Length	355 mm	Width	245 mm	Height	42 mm
Rectangular Luminous Area		Length	355 mm	Width	41 mm	Height	25 mm
Horizontal Luminous Area		0.014555 m2		Emitting area on Plane 180°		0.008875 m2	
Emitting area on Plane 0°		0.008875 m2		Emitting area on Plane 270°		0.001025 m2	
Emitting area on Plane 90°		0.001025 m2		Glare area at 76°		0.012133 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		19-12-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		616 lm	
LED Flux=778lm LED Power=6W Eff=79% EfcLed=130lm/W EfcLum=103lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	36 65 86 72 100			D DIN 5040	B21		
F UTE	0.72 H + 0.28 T			B NBN	BZ 6		


355mm x 245mm



Semipiani C

180.0 ——— 0.0  
270.0 ——— 90.0

ULOR 27.80 %  
DLOR 72.20 %  
RN 27.80 %



## Luminaire

Code 1215L00A  
Name AOL MINI W L UPPERCASE

## Measurerm.


Code FTS2400018  
Name AOL MINI W L UPPERCASE

Luminaire Flux	616 lm	Luminaire Power	6.0 W	Efficacy	102.667 lm/W	Efficiency	100.00%
Source Flux	616 lm	Maximum value	186.86 cd/klm	Position	C=65.00 G=2.00	CG	Asymmetrical
Rectangular Luminaire		Length	355 mm	Width	245 mm	Height	42 mm
Rectangular Luminous Area		Length	355 mm	Width	41 mm	Height	25 mm
Horizontal Luminous Area	0.014555 m2			Emitting area on Plane 180°		0.008875 m2	
Emitting area on Plane 0°	0.008875 m2			Emitting area on Plane 270°		0.001025 m2	
Emitting area on Plane 90°	0.001025 m2			Glare area at 76°		0.012133 m2	
Coordinate system	CG			Symmetry Type		Asymmetrical	
Date	19-12-2023			Maximum Gamma Angle		180	
Measurement Distance	0.00			Measurement Flux		616 lm	
LED Flux=778lm LED Power=6W Eff=79% EfcLed=130lm/W EfcLum=103lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	36 65 86 72 100			D DIN 5040	B21		
F UTE	0.72 H + 0.28 T			B NBN	BZ 6		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	4.80	9.60	14.40	19.21	24.01	OC	1.91	3.81	5.72	7.62	9.53
OB	4.80	9.60	14.40	19.21	24.01	OD	1.91	3.81	5.72	7.62	9.53

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	115.09	114.73	112.33	107.54	100.57	92.03	82.38	72.29	61.25	49.97
OB	115.09	114.73	112.33	107.54	100.57	92.03	82.38	72.29	61.25	49.97
OC	115.09	114.56	111.16	104.39	94.81	82.66	68.69	53.44	37.83	23.83
OD	115.09	114.56	111.16	104.39	94.81	82.66	68.69	53.44	37.83	23.83



H[m]	D[m]	Max lux	Med lux	Alpha=78.2°+78.2°	G=0.0
1.00	9.60	115	10		
2.00	19.21	29	2		
3.00	28.81	13	1		
4.00	38.41	7	1		
5.00	48.01	5	0		

H[m]	D[m]	Max lux	Med lux	Beta=62.3°+62.3°	G=0.0
1.00	3.81	115	10		
2.00	7.62	29	2		
3.00	11.43	13	1		
4.00	15.25	7	1		
5.00	19.06	5	0		