

## Luminaire

Code 1284010A  
Name nh 14 C

## Measurement

Code FTS2000225-A  
Name nh 14 C

Luminaire Flux	378 lm	Luminaire Power	5.0 W	Efficacy	75.569 lm/W	Efficiency	80.39%
Source Flux	470 lm	Maximum value	122.51 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Round Luminaire		Diam.	140 mm	Height	140 mm		
Round Luminous Area		Diam.	140 mm	Height	140 mm		
Horizontal Luminous Area		0.015394 m <sup>2</sup>		Emitting area on Plane 180°		0.019600 m <sup>2</sup>	
Emitting area on Plane 0°		0.019600 m <sup>2</sup>		Emitting area on Plane 270°		0.019600 m <sup>2</sup>	
Emitting area on Plane 90°		0.019600 m <sup>2</sup>		Glare area at 76°		0.022742 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		18-01-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		470 lm	

Lamping=LED 1x5W (E14) CCT=2700K CRI=80

C.I.E. 32 59 81 70 80  
F UTE 0.56 H + 0.24 T

D DIN 5040  
B NBN

B21  
BZ 7 / 0.8 / BZ 6 / 1.25 / BZ 7 / 2.5 / BZ 6 / 3 / BZ 7

Diam=140mm



Semipiani C

180.0 ——— 0.0

ULOR 24.07 %

DLOR 56.32 %

RN 29.94 %

