

Luminaire


Code 1305000A
Name ALPHABET OF LIGHT C/W LINEARE 180

Measurement

Code FTS1701419-A
Name ALPHABET OF LIGHT C/W LINEARE 180

Luminaire Flux	5226 lm	Luminaire Power	39.0 W	Efficacy	134.000 lm/W	Efficiency	100.00%
Source Flux	5226 lm	Maximum value	158.36 cd/klm	Position	C=45.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.090000 m2		Emitting area on Plane 180°		0.090000 m2	
Emitting area on Plane 0°		0.090000 m2		Emitting area on Plane 270°		0.002500 m2	
Emitting area on Plane 90°		0.002500 m2		Glare area at 76°		0.109100 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		24-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5226 lm	
LED Flux=6451lm LED Power=35W Eff=81% EfcLed=184lm/W EfcLum=134lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h							
C.I.E.	33 60 83 69 100			D DIN 5040	B21		
F UTE	0.69 H + 0.31 T			B NBN	BZ 6		

1800mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 30.60 %
DLOR 69.40 %
RN 30.60 %

