

Luminaire


Code 1426000A
Name ALPHABET OF LIGHT SR LINEARE 180 EU-USA

Measurement

Code FTS1900832-A
Name ALPHABET OF LIGHT SR LINEARE 180 EU-USA

Luminaire Flux	5226 lm	Luminaire Power	35.0 W	Efficacy	149.314 lm/W	Efficiency	100.00%
Source Flux	5226 lm	Maximum value	158.36 cd/klm	Position	C=45.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.090000 m ²		Emitting area on Plane 180°		0.090000 m ²	
Emitting area on Plane 0°		0.090000 m ²		Emitting area on Plane 270°		0.002500 m ²	
Emitting area on Plane 90°		0.002500 m ²		Glare area at 76°		0.109100 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		24-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5226 lm	
LED Flux=6451lm LED Power=35W Eff=81% EfcLed=184lm/W EfcLum=149lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h							
C.I.E.	33 60 83 69 100			D DIN 5040		B21	
F UTE	0.69 H + 0.31 T			B NBN		BZ 6	

1800mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 30.60 %

DLOR 69.40 %

RN 30.60 %

