

Luminaire

Code 1645080APP
 Name ILIO MINI LED F APP 3000K NRO OPACO

Measurement

Code FTS2103006
 Name ILIO MINI LED F APP 3000K NRO OPACO

Luminaire Flux	1528 lm	Luminaire Power	23.0 W	Efficacy	66.414 lm/W	Efficiency	100.00%
Source Flux	1528 lm	Maximum value	559.22 cd/klm	Position	C=0.00 G=180.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	1737 mm		
Round Luminous Area		Diam.	30 mm	Height	0 mm		
Horizontal Luminous Area		0.000707 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.000171 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		08-07-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1528 lm	
LED Flux=2182lm LED Power=21W Eff=70% EfcLed=106lm/W EfcLum=66lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(6K)=66000h							
C.I.E.	0 0 0 0 100			D DIN 5040	--		
F UTE	1.00 T			B NBN	BZ 10		

Diam=40mm



Semipiani C

180.0 ——— 0.0

ULOR100.00 %

DLOR 0.00 %

RN100.00 %



