


## Luminaire

Code 2001030APP\_G  
Name DISCOVERY SPACE 90X90 S RGBW APP COMP NR - GREEN


## Measurement

Code FTS2000463-B  
Name DISCOVERY SPACE 90X90 S RGBW APP COMP NR - GREEN

Luminaire Flux	395 lm	Luminaire Power	11.0 W	Efficacy	35.909 lm/W	Efficiency	100.00%
Source Flux	395 lm	Maximum value	149.86 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	970 mm	Width	970 mm	Height	17 mm
Rectangular Luminous Area		Length	900 mm	Width	900 mm	Height	10 mm
Horizontal Luminous Area		0.810000 m <sup>2</sup>		Emitting area on Plane 180°		0.009000 m <sup>2</sup>	
Emitting area on Plane 0°		0.009000 m <sup>2</sup>		Emitting area on Plane 270°		0.009000 m <sup>2</sup>	
Emitting area on Plane 90°		0.009000 m <sup>2</sup>		Glare area at 76°		0.204689 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		14-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		395 lm	
LED Flux=703lm LED Power=8W Eff=56% EfcLed=93lm/W EfcLum=35lm/W L70(6K)=60000h							
C.I.E.	41 72 92 50 100			D DIN 5040		C31	
F UTE	0.50 G + 0.50 T			B NBN		BZ 5	



ULOR 49.86 %  
DLOR 50.14 %  
RN 49.86 %



## Luminaire

Code 2001030APP\_G  
Name DISCOVERY SPACE 90X90 S RGBW APP COMP NR - GREEN

## Measurerm.


Code FTS2000463-B  
Name DISCOVERY SPACE 90X90 S RGBW APP COMP NR - GREEN

Luminaire Flux	395 lm	Luminaire Power	11.0 W	Efficacy	35.909 lm/W	Efficiency	100.00%
Source Flux	395 lm	Maximum value	149.86 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	970 mm	Width	970 mm	Height	17 mm
Rectangular Luminous Area		Length	900 mm	Width	900 mm	Height	10 mm
Horizontal Luminous Area		0.810000 m2		Emitting area on Plane 180°		0.009000 m2	
Emitting area on Plane 0°		0.009000 m2		Emitting area on Plane 270°		0.009000 m2	
Emitting area on Plane 90°		0.009000 m2		Glare area at 76°		0.204689 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		14-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		395 lm	
LED Flux=703lm LED Power=8W Eff=56% EfcLed=93lm/W EfcLum=35lm/W L70(6K)=60000h							
C.I.E.	41 72 92 50 100			D DIN 5040		C31	
F UTE	0.50 G + 0.50 T			B NBN		BZ 5	

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	2.09	4.18	6.26	8.35	10.44	OC	1.91	3.83	5.74	7.65	9.57
OB	2.09	4.18	6.26	8.35	10.44	OD	1.91	3.83	5.74	7.65	9.57

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	59.20	59.02	57.10	53.54	48.57	42.78	36.42	29.15	20.47	9.89
OB	59.20	59.02	57.10	53.54	48.57	42.78	36.42	29.15	20.47	9.89
OC	59.20	59.02	57.30	53.98	49.15	43.19	35.76	27.27	17.58	7.16
OD	59.20	59.02	57.30	53.98	49.15	43.19	35.76	27.27	17.58	7.16



H[m]	D[m]	Max lux	Med lux	Alpha=64.4°+64.4°	G=0.0
1.00	4.18	59	10		
2.00	8.35	15	2		
3.00	12.53	7	1		
4.00	16.70	4	1		
5.00	20.88	2	0		

H[m]	D[m]	Max lux	Med lux	Beta=62.4°+62.4°	G=0.0
1.00	3.83	59	10		
2.00	7.65	15	2		
3.00	11.48	7	1		
4.00	15.31	4	1		
5.00	19.13	2	0		