

Luminaire


Code 2123010AHE
Name AOL SYSTEM S 60° SLV INT 3000K HE

Measurement

Code FTS2400059
Name AOL SYSTEM S 60° SLV INT 3000K HE

| | | | | | | | |
|---|-----------------|-------------------------|---------------|-----------------------------|----------------|-------------------------|----------------------|
| Luminaire Flux | 815 lm | Luminaire Power | 8.0 W | Efficacy | 101.875 lm/W | Efficiency | 100.00% |
| Source Flux | 815 lm | Maximum value | 162.58 cd/klm | Position | C=20.00 G=5.00 | CG | Sym. on planes 0-180 |
| Rectangular Luminaire | | Length | 475 mm | Width | 50 mm | Height | 50 mm |
| Rectangular Luminous Area | | Length | 475 mm | Width | 50 mm | Height | 50 mm |
| Horizontal Luminous Area | | 0.023750 m ² | | Emitting area on Plane 180° | | 0.023750 m ² | |
| Emitting area on Plane 0° | | 0.023750 m ² | | Emitting area on Plane 270° | | 0.002500 m ² | |
| Emitting area on Plane 90° | | 0.002500 m ² | | Glare area at 76° | | 0.028790 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Sym. on planes 0-180 | |
| Date | | 26-03-2024 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 815 lm | |
| LED Flux=1066lm LED Power=8W Eff=76% EfcLed=133lm/W EfcLum=102lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(10k)=60000h | | | | | | | |
| C.I.E. | 33 61 83 70 100 | | | D DIN 5040 | B21 | | |
| F UTE | 0.70 H + 0.30 T | | | B NBN | BZ 6 | | |

475mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 30.45 %
DLOR 69.55 %
RN 30.45 %

