

Luminaire

Code 2131C10AHE
Name AOL SYSTEM C/W LIN.60 SLV TER 3500K HE

Measurement

Code FTS2400065
Name AOL SYSTEM C/W LIN.60 SLV TER 3500K HE

Luminaire Flux	1133 lm	Luminaire Power	11.0 W	Efficacy	103.000 lm/W	Efficiency	100.00%
Source Flux	1133 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical
Rectangular Luminaire		Length	580 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	580 mm	Width	50 mm	Height	49 mm
Horizontal Luminous Area		0.029000 m ²		Emitting area on Plane 180°		0.029000 m ²	
Emitting area on Plane 0°		0.029000 m ²		Emitting area on Plane 270°		0.002500 m ²	
Emitting area on Plane 90°		0.002500 m ²		Glare area at 76°		0.035154 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		26-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1133 lm	
LED Flux=1421lm LED Power=11W Eff=80% EfcLed=129lm/W EfcLum=103lm/W CCT=3500K Ra=90 R9=50 SDCM=3 L70(10k)=60000h							
C.I.E.	33 60 82 69 100			D DIN 5040		B21	
F UTE	0.69 H + 0.31 T			B NBN		BZ 6	

