

## Luminaire

Code 2140C10AHE  
Name AOL SYSTEM C/W LIN.180 SLV TER 3500K HE

## Measurement

Code FTS2400067  
Name AOL SYSTEM C/W LIN.180 SLV TER 3500K HE

Luminaire Flux	3400 lm	Luminaire Power	33.0 W	Efficacy	103.030 lm/W	Efficiency	100.00%
Source Flux	3400 lm	Maximum value	156.12 cd/klm	Position	C=5.00 G=5.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1800 mm	Width	50 mm	Height	50 mm
Rectangular Luminous Area		Length	1800 mm	Width	50 mm	Height	50 mm
Horizontal Luminous Area		0.090000 m <sup>2</sup>		Emitting area on Plane 180°		0.090000 m <sup>2</sup>	
Emitting area on Plane 0°		0.090000 m <sup>2</sup>		Emitting area on Plane 270°		0.002500 m <sup>2</sup>	
Emitting area on Plane 90°		0.002500 m <sup>2</sup>		Glare area at 76°		0.109100 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		26-03-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3400 lm	


LED Flux=4262lm LED Power=33W Eff=80% EfcLed=129lm/W EfcLum=103lm/W CCT=3500K Ra=90 R9=50 SDCM=3 L70(10k)=60000h

C.I.E. 33 60 82 69 100  
F UTE 0.69 H + 0.31 T

D DIN 5040  
B NBN

B21  
BZ 6

1800mm x 50mm



Sempiani C

180.0 ——— 0.0  
270.0 ——— 90.0

ULOR 31.35 %

DLOR 68.65 %

RN 31.35 %

