

Luminaire


Code 2608C10AHE
Name AOL SYSTEM C/W 22° MAST TER SX 3500K HE

Measurement

Code FTS2400482
Name AOL SYSTEM C/W 22° MAST TER SX 3500K HE

| | | | | | | | |
|--|-----------------|-------------------------|---------------|-----------------------------|----------------|-------------------------|--------------------|
| Luminaire Flux | 1169 lm | Luminaire Power | 11.0 W | Efficacy | 106.269 lm/W | Efficiency | 100.00% |
| Source Flux | 1169 lm | Maximum value | 159.90 cd/klm | Position | C=15.00 G=2.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 685 mm | Width | 50 mm | Height | 50 mm |
| Rectangular Luminous Area | | Length | 685 mm | Width | 50 mm | Height | 49 mm |
| Horizontal Luminous Area | | 0.034250 m ² | | Emitting area on Plane 180° | | 0.034250 m ² | |
| Emitting area on Plane 0° | | 0.034250 m ² | | Emitting area on Plane 270° | | 0.002500 m ² | |
| Emitting area on Plane 90° | | 0.002500 m ² | | Glare area at 76° | | 0.041518 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 12-09-2024 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1169 lm | |
| LED Flux=1421lm LED Power=11W Eff=82% EfcLed=129lm/W EfcLum=106lm/W CCT=3500K Ra=90 R9=50 SDCM=3 L70(10k)=60000h | | | | | | | |
| C.I.E. | 33 60 83 70 100 | | | D DIN 5040 | | B21 | |
| F UTE | 0.70 H + 0.30 T | | | B NBN | | BZ 6 | |

685mm x 50mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 29.66 %
DLOR 70.34 %
RN 29.66 %

