

Luminaire


Code AF00605+AF95004
 Name SHARP RECESSED TRIM 1X 3W 940 FLOOD SILVER EXT.DRV + SCREEN 1X BLACK

Measurem.

Code FTS1603224
 Name SHARP RECESSED TRIM 1X 3W 940 FLOOD SILVER EXT.DRV + SCREEN 1X BLACK

Luminaire Flux	211.68 lm	Luminaire Power	3.00 W	Efficacy	70.56 lm/W	Efficiency	100.00%
Lamps Flux	211.68 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	40 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	37 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.001369 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000331 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		211.68 lm	
LED Flux=283,99lm LED Power=3W Eff=75% EfcLed=95lm/W EfcLum=71lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	100 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		


40mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR100.00 %
 RN 0.00 %



Luminaire

Code AF00605+AF95004
 Name SHARP RECESSED TRIM 1X 3W 940 FLOOD SILVER EXT.DRV + SCREEN 1X BLACK

Measurerm.


Code FTS1603224
 Name SHARP RECESSED TRIM 1X 3W 940 FLOOD SILVER EXT.DRV + SCREEN 1X BLACK

Luminaire Flux	211.68 lm	Luminaire Power	3.00 W	Efficacy	70.56 lm/W	Efficiency	100.00%
Lamps Flux	211.68 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	40 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	37 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.001369 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000331 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		211.68 lm	
LED Flux=283,99lm LED Power=3W Eff=75% EfcLed=95lm/W EfcLum=71lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1186.34	1008.79	309.73	82.85	4.91	1.04	0.13	0.00	0.00	0.00
OB	1186.34	1008.79	309.73	82.85	4.91	1.04	0.13	0.00	0.00	0.00
OC	1186.34	1008.79	309.73	82.85	4.91	1.04	0.13	0.00	0.00	0.00
OD	1186.34	1008.79	309.73	82.85	4.91	1.04	0.13	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	1186	757		
2.00	0.70	297	189		
3.00	1.05	132	84		
4.00	1.40	74	47		
5.00	1.75	47	30		