

## Luminaire

Code AF15704  
Name SHARP RCS.TRIM.8X 22W 930 WW NRO/NRO

## Measur.

Code FTS2000136  
Name SHARP RCS.TRIM.8X 22W 930 WW NRO/NRO

|   |                  |                 |                |                             |                 |                      |                      |
|---|------------------|-----------------|----------------|-----------------------------|-----------------|----------------------|----------------------|
| Luminaire Flux  | 1312.91 lm       | Luminaire Power | 22.00 W        | Efficacy                    | 59.68 lm/W      | Efficiency           | 100.00%              |
| Lamps Flux  | 1312.91 lm       | Maximum value   | 1103.17 cd/klm | Position                    | C=175.00 G=9.00 | CG                   | Sym. on planes 0-180 |
| Rectangular Luminaire   |                  | Length          | 300 mm         | Width                       | 45 mm           | Height               | 85 mm                |
| Rectangular Luminous Area   |                  | Length          | 290 mm         | Width                       | 32 mm           | Height               | 0 mm                 |
| Horizontal Luminous Area  |                  | 0.009280 m2     |                | Emitting area on Plane 180° |                 | 0.000000 m2          |                      |
| Emitting area on Plane 0°   |                  | 0.000000 m2     |                | Emitting area on Plane 270° |                 | 0.000000 m2          |                      |
| Emitting area on Plane 90°  |                  | 0.000000 m2     |                | Glare area at 76°           |                 | 0.002245 m2          |                      |
| Coordinate system   |                  | CG              |                | Symmetry Type               |                 | Sym. on planes 0-180 |                      |
| Date  |                  | 29-10-2019      |                | Maximum Gamma Angle         |                 | 180                  |                      |
| Measurement Distance  |                  | 0.00            |                | Measurement Flux            |                 | 1312.91 lm           |                      |
| LED Flux=2186lm LED Power=22W Eff=60% EfcLed=99lm/W EfcLum=60lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h |                  |                 |                |                             |                 |                      |                      |
| C.I.E.  | 73 92 98 100 100 |                 |                | D DIN 5040                  | A60             |                      |                      |
| F UTE   | 1.00 B           |                 |                | B NBN                       | BZ 1 / 1 / BZ 2 |                      |                      |



