

Luminaire

Code AF20305+AF95201+AF0600
 Name SHARP RECESSED TRIM 12X 36W 940 FLOOD SILVER EXT.DRV + SCREEN 4X WHITE + GRAZER LENS

Measurerm.

Code FTS1901408
 Name SHARP RECESSED TRIM 12X 36W 940 FLOOD SILVER EXT.DRV + SCREEN 4X WHITE + GRAZER LENS

| | | | | | | | |
|---|------------------|-----------------|----------------|-----------------------------|-----------------|--------------------|--------------------|
| Luminaire Flux | 2385.60 lm | Luminaire Power | 33.00 W | Efficacy | 72.29 lm/W | Efficiency | 100.00% |
| Lamps Flux | 2385.60 lm | Maximum value | 1469.14 cd/klm | Position | C=90.00 G=23.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 464 mm | Width | 40 mm | Height | 55 mm |
| Rectangular Luminous Area | | Length | 444 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.016428 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.003974 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 18-07-2018 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 2385.60 lm | |
| LED Flux=3407.94lm LED Power=33W Eff=70% EfcLed=103lm/W EfcLum=72lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h | | | | | | | |
| C.I.E. | 89 97 99 100 100 | | | D DIN 5040 | A60 | | |
| F UTE | 1.00 A | | | B NBN | BZ 1 | | |



