

Luminaire


Code AF36801+AF95104
 Name SHARP SMD.2X 5,5W 940 XF EXD BCO+ SCREEN 2X BLACK

Measurem.

Code FTS1902105
 Name SHARP SMD.2X 5,5W 940 XF EXD BCO+ SCREEN 2X BLACK

Luminaire Flux	406.91 lm	Luminaire Power	6.50 W	Efficacy	62.60 lm/W	Efficiency	100.00%
Lamps Flux	406.91 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	78 mm	Width	45 mm	Height	90 mm
Rectangular Luminous Area		Length	72 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.002664 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000644 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		406.91 lm	
LED Flux=567.99lm LED Power=6.5W Eff=72% EfcLed=87lm/W EfcLum=63lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	


78mm x 45mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code AF36801+AF95104
Name SHARP SMD.2X 5,5W 940 XF EXD BCO+ SCREEN 2X BLACK

Measur.


Code FTS1902105
Name SHARP SMD.2X 5,5W 940 XF EXD BCO+ SCREEN 2X BLACK

Luminaire Flux	406.91 lm	Luminaire Power	6.50 W	Efficacy	62.60 lm/W	Efficiency	100.00%
Lamps Flux	406.91 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	78 mm	Width	45 mm	Height	90 mm
Rectangular Luminous Area		Length	72 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.002664 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000644 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		406.91 lm	
LED Flux=567.99lm LED Power=6.5W Eff=72% EfcLed=87lm/W EfcLum=63lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	582.27	578.09	527.83	351.10	62.17	9.07	0.71	0.00	0.00	0.00
OB	582.27	578.09	527.83	351.10	62.17	9.07	0.71	0.00	0.00	0.00
OC	582.27	578.09	527.83	351.10	62.17	9.07	0.71	0.00	0.00	0.00
OD	582.27	578.09	527.83	351.10	62.17	9.07	0.71	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0
1.00	0.98	582	351		
2.00	1.96	146	88		
3.00	2.93	65	39		
4.00	3.91	36	22		
5.00	4.89	23	14		