

## Luminaire


Code AF41301+AF95201  
 Name SHARP SMD.4X 11W 930 FL EXD BCO+ SCREEN 4X WHITE

## Measurem.

Code FTS1901875  
 Name SHARP SMD.4X 11W 930 FL EXD BCO+ SCREEN 4X WHITE

Luminaire Flux	803.84 lm	Luminaire Power	12.00 W	Efficacy	66.99 lm/W	Efficiency	100.00%
Lamps Flux	803.84 lm	Maximum value	5541.55 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	152 mm	Width	45 mm	Height	90 mm
Rectangular Luminous Area		Length	148 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.005476 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001325 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		803.84 lm	
LED Flux=1061.32lm LED Power=12W Eff=76% EfcLed=88lm/W EfcLum=67lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	


152mm x 45mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



## Luminaire

Code AF41301+AF95201  
Name SHARP SMD.4X 11W 930 FL EXD BCO+ SCREEN 4X WHITE

## Measurement


Code FTS1901875  
Name SHARP SMD.4X 11W 930 FL EXD BCO+ SCREEN 4X WHITE

Luminaire Flux	803.84 lm	Luminaire Power	12.00 W	Efficacy	66.99 lm/W	Efficiency	100.00%
Lamps Flux	803.84 lm	Maximum value	5541.55 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	152 mm	Width	45 mm	Height	90 mm
Rectangular Luminous Area		Length	148 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.005476 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001325 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		803.84 lm	
LED Flux=1061.32lm LED Power=12W Eff=76% EfcLed=88lm/W EfcLum=67lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4454.52	3790.81	1169.51	319.77	20.06	5.66	1.97	1.26	0.89	0.42
OB	4454.52	3790.81	1169.51	319.77	20.06	5.66	1.97	1.26	0.89	0.42
OC	4454.52	3790.81	1169.51	319.77	20.06	5.66	1.97	1.26	0.89	0.42
OD	4454.52	3790.81	1169.51	319.77	20.06	5.66	1.97	1.26	0.89	0.42



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	4455	2840		
2.00	0.70	1114	710		
3.00	1.05	495	316		
4.00	1.41	278	178		
5.00	1.76	178	114		