


## Luminaire

Code AF75000+AF95204  
 Name SHARP RECESSED TRIMLESS 16X 48W 930 FLOOD EXT.DRV + SCREEN 4X BLACK

## Measurem.

Code FTS1603347  
 Name SHARP RECESSED TRIMLESS 16X 48W 930 FLOOD EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	3163.98 lm	Luminaire Power	44.00 W	Efficacy	71.91 lm/W	Efficiency	100.00%
Lamps Flux	3163.98 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	612 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area			0.021904 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.005299 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3163.98 lm	
LED Flux=4245,28lm LED Power=44W Eff=75% EfcLed=96lm/W EfcLum=72lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	100	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



## Luminaire

Code AF75000+AF95204  
 Name SHARP RECESSED TRIMLESS 16X 48W 930 FLOOD EXT.DRV + SCREEN 4X BLACK

## Measurerm.


Code FTS1603347  
 Name SHARP RECESSED TRIMLESS 16X 48W 930 FLOOD EXT.DRV + SCREEN 4X BLACK

Luminaire Flux	3163.98 lm	Luminaire Power	44.00 W	Efficacy	71.91 lm/W	Efficiency	100.00%
Lamps Flux	3163.98 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	612 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3163.98 lm	
LED Flux=4245,28lm LED Power=44W Eff=75% EfcLed=96lm/W EfcLum=72lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	17732.28	15078.41	4629.54	1238.39	73.32	15.51	1.95	0.00	0.00	0.00
OB	17732.28	15078.41	4629.54	1238.39	73.32	15.51	1.95	0.00	0.00	0.00
OC	17732.28	15078.41	4629.54	1238.39	73.32	15.51	1.95	0.00	0.00	0.00
OD	17732.28	15078.41	4629.54	1238.39	73.32	15.51	1.95	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	17732	11314		
2.00	0.70	4433	2828		
3.00	1.05	1970	1257		
4.00	1.40	1108	707		
5.00	1.75	709	453		