


Luminaire

Code AF81301+AF95204
Name SHARP SMD.12X 33W 940 FL ND BCO+ SCREEN 4X BLACK

Measurem.

Code FTS1800912
Name SHARP SMD.12X 33W 940 FL ND BCO+ SCREEN 4X BLACK

Luminaire Flux	2539.94 lm	Luminaire Power	37.00 W	Efficacy	68.65 lm/W	Efficiency	100.00%
Lamps Flux	2539.94 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	464 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003974 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2539.94 lm	
LED Flux=3407.94lm LED Power=33W Eff=75% EfcLed=103lm/W EfcLum=69lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	100	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



Luminaire

Code AF81301+AF95204
Name SHARP SMD.12X 33W 940 FL ND BCO+ SCREEN 4X BLACK

Measurement


Code FTS1800912
Name SHARP SMD.12X 33W 940 FL ND BCO+ SCREEN 4X BLACK

Luminaire Flux	2539.94 lm	Luminaire Power	37.00 W	Efficacy	68.65 lm/W	Efficiency	100.00%
Lamps Flux	2539.94 lm	Maximum value	5604.42 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	464 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003974 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2539.94 lm	
LED Flux=3407.94lm LED Power=33W Eff=75% EfcLed=103lm/W EfcLum=69lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	100	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	14234.90	12104.45	3716.44	994.14	58.86	12.45	1.57	0.00	0.00	0.00
OB	14234.90	12104.45	3716.44	994.14	58.86	12.45	1.57	0.00	0.00	0.00
OC	14234.90	12104.45	3716.44	994.14	58.86	12.45	1.57	0.00	0.00	0.00
OD	14234.90	12104.45	3716.44	994.14	58.86	12.45	1.57	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	14235	9082		
2.00	0.70	3559	2271		
3.00	1.05	1582	1009		
4.00	1.40	890	568		
5.00	1.75	569	363		