


Luminaire

Code AF81504+AF95204
 Name SHARP SMD.12X 33W 940 XF ND NRO+ SCREEN 4X BLACK

Measurem.

Code FTS1800919
 Name SHARP SMD.12X 33W 940 XF ND NRO+ SCREEN 4X BLACK

Luminaire Flux	2441.46 lm	Luminaire Power	37.00 W	Efficacy	65.99 lm/W	Efficiency	100.00%
Lamps Flux	2441.46 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	464 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003974 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2441.46 lm	
LED Flux=3407.94lm LED Power=33W Eff=72% EfcLed=103lm/W EfcLum=66lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



Luminaire

Code AF81504+AF95204
Name SHARP SMD.12X 33W 940 XF ND NRO+ SCREEN 4X BLACK

Measurement


Code FTS1800919
Name SHARP SMD.12X 33W 940 XF ND NRO+ SCREEN 4X BLACK

Luminaire Flux	2441.46 lm	Luminaire Power	37.00 W	Efficacy	65.99 lm/W	Efficiency	100.00%
Lamps Flux	2441.46 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	464 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003974 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2441.46 lm	
LED Flux=3407.94lm LED Power=33W Eff=72% EfcLed=103lm/W EfcLum=66lm/W CCT=4000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	3493.65	3468.53	3167.00	2106.58	373.00	54.41	4.24	0.00	0.00	0.00
OB	3493.65	3468.53	3167.00	2106.58	373.00	54.41	4.24	0.00	0.00	0.00
OC	3493.65	3468.53	3167.00	2106.58	373.00	54.41	4.24	0.00	0.00	0.00
OD	3493.65	3468.53	3167.00	2106.58	373.00	54.41	4.24	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0
1.00	0.98	3494	2109		
2.00	1.96	873	527		
3.00	2.93	388	234		
4.00	3.91	218	132		
5.00	4.89	140	84		