

Luminaire

Code AF83005
Name SHARP SMD.12X 33W 930 WW DIM SIL/NRO

Measurem.

Code FTS1903529
Name SHARP SMD.12X 33W 930 WW DIM SIL/NRO

Luminaire Flux	1969.35 lm	Luminaire Power	37.00 W	Efficacy	53.23 lm/W	Efficiency	100.00%
Lamps Flux	1969.35 lm	Maximum value	1103.17 cd/klm	Position	C=175.00 G=9.00	CG	Sym. on planes 0-180
Rectangular Luminaire		Length	450 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	440 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area		0.014080 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.003406 m ²	
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		29-10-2019		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1969.35 lm	


LED Flux=3279lm LED Power=33W Eff=60% EfcLed=99lm/W EfcLum=53lm/W CCT=3000K Ra=90 SDCM=2 L70(6K)=118000h

C.I.E. 73 92 98 100 100
F UTE 1.00 B

D DIN 5040
B NBN

A60
BZ 1 / 1 / BZ 2

450mm x 45mm



Semipiani C

180.0 ——— 0.0
270.0 ——— 90.0

ULOR 0.18 %
DLOR 99.82 %
RN 0.18 %

