

Luminaire


Code AF87205+AF95201
Name SHARP SMD.16X 44W 930 XF DIM SIL+ SCREEN 4X WHITE

Measurem.

Code FTS1800857
Name SHARP SMD.16X 44W 930 XF DIM SIL+ SCREEN 4X WHITE

Luminaire Flux	3115.61 lm	Luminaire Power	47.00 W	Efficacy	66.29 lm/W	Efficiency	100.00%
Lamps Flux	3115.61 lm	Maximum value	1406.35 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	612 mm	Width	40 mm	Height	55 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3115.61 lm	
LED Flux=4245.28lm LED Power=44W Eff=73% EfcLed=96lm/W EfcLum=66lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

612mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %

