

## Luminaire

Code AF87801+AF95204  
 Name SHARP SMD.16X 44W 927 XF DIM BCO+ SCREEN 4X BLACK

## Measurem.

Code FTS1902213-A  
 Name SHARP SMD.16X 44W 927 XF DIM BCO+ SCREEN 4X BLACK

Luminaire Flux	3039 lm	Luminaire Power	47.0 W	Efficacy	64.653 lm/W	Efficiency	100.00%
Source Flux	3039 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	596 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		25-11-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3039 lm	


LED Flux=4242lm LED Power=44W Eff=72% EfcLed=96lm/W EfcLum=65lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=272160h

C.I.E. 99 100 100 100 100  
 F UTE --

D DIN 5040  
 B NBN

A60  
 BZ 1


596mm x 45mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



## Luminaire

Code AF87801+AF95204  
Name SHARP SMD.16X 44W 927 XF DIM BCO+ SCREEN 4X BLACK

## Measurerm.


Code FTS1902213-A  
Name SHARP SMD.16X 44W 927 XF DIM BCO+ SCREEN 4X BLACK

Luminaire Flux	3039 lm	Luminaire Power	47.0 W	Efficacy	64.653 lm/W	Efficiency	100.00%
Source Flux	3039 lm	Maximum value	1430.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	596 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		25-11-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3039 lm	
LED Flux=4242lm LED Power=44W Eff=72% EfcLed=96lm/W EfcLum=65lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=272160h							
C.I.E.	99	100	100	100		D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	4348.25	4316.99	3941.70	2621.89	464.24	67.72	5.28	0.00	0.00	0.00
OB	4348.25	4316.99	3941.70	2621.89	464.24	67.72	5.28	0.00	0.00	0.00
OC	4348.25	4316.99	3941.70	2621.89	464.24	67.72	5.28	0.00	0.00	0.00
OD	4348.25	4316.99	3941.70	2621.89	464.24	67.72	5.28	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0
1.00	0.98	4348	2624		
2.00	1.96	1087	656		
3.00	2.93	483	292		
4.00	3.91	272	164		
5.00	4.89	174	105		