

## Luminaire

Code AG07604  
 Name SMART OFFICE SUSPENSION DIR + IND 2249mm 840 DARKLIGHT DIM BLACK

## Measurerm.

Code FTS1603413  
 Name SMART OFFICE SUSPENSION DIR + IND 2249mm 840 DARKLIGHT DIM BLACK

|  |                  |                 |               |                             |                |                    |                    |
|--|------------------|-----------------|---------------|-----------------------------|----------------|--------------------|--------------------|
| Luminaire Flux   | 9128.00 lm       | Luminaire Power | 76.00 W       | Efficacy                    | 120.11 lm/W    | Efficiency         | 100.00%            |
| Lamps Flux   | 9128.00 lm       | Maximum value   | 329.16 cd/klm | Position                    | C=50.00 G=4.00 | CG                 | Double Symmetrical |
| Rectangular Luminaire  |                  | Length          | 2249 mm       | Width                       | 65 mm          | Height             | 90 mm              |
| Rectangular Luminous Area  |                  | Length          | 2199 mm       | Width                       | 55 mm          | Height             | 0 mm               |
| Horizontal Luminous Area   |                  | 0.120945 m2     |               | Emitting area on Plane 180° |                | 0.000000 m2        |                    |
| Emitting area on Plane 0°  |                  | 0.000000 m2     |               | Emitting area on Plane 270° |                | 0.000000 m2        |                    |
| Emitting area on Plane 90°   |                  | 0.000000 m2     |               | Glare area at 76°           |                | 0.029259 m2        |                    |
| Coordinate system  |                  | CG              |               | Symmetry Type               |                | Double Symmetrical |                    |
| Date   |                  | 26-04-2017      |               | Maximum Gamma Angle         |                | 180                |                    |
| Measurement Distance   |                  | 0.00            |               | Measurement Flux            |                | 9128.00 lm         |                    |
| LED Flux=12000lm LED Power=66W Eff=76% EfcLed=182lm/W EfcLum=120lm/W Ra=80 SDCM=3 L70(6K)=50000h |                  |                 |               |                             |                |                    |                    |
| C.I.E.   | 70 99 100 63 100 |                 |               | D DIN 5040                  |                | B51                |                    |
| F UTE  | 0.63 C + 0.37 T  |                 |               | B NBN                       |                | BZ 2               |                    |



