

Luminaire

Code AN10720+AP91400
 Name VECTOR 55 TRACK 930 FL DALI BR.BRONZE + ANTI-DAZZLE LOUVRE

Measurement

Code FTS1800398-B
 Name VECTOR 55 TRACK 930 FL DALI BR.BRONZE + ANTI-DAZZLE LOUVRE

| | | | | | | | |
|--|---------|-------------------------|----------------|-----------------------------|---------------|-------------------------|-----------------|
| Luminaire Flux | 1277 lm | Luminaire Power | 20.0 W | Efficacy | 63.850 lm/W | Efficiency | 100.00% |
| Source Flux | 1277 lm | Maximum value | 6688.13 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Round Luminaire | | Diam. | 55 mm | Height | 130 mm | | |
| Round Luminous Area | | Diam. | 48 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.001810 m ² | | Emitting area on Plane 180° | | 0.000000 m ² | |
| Emitting area on Plane 0° | | 0.000000 m ² | | Emitting area on Plane 270° | | 0.000000 m ² | |
| Emitting area on Plane 90° | | 0.000000 m ² | | Glare area at 76° | | 0.000438 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 28-02-2024 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1277 lm | |
| LED Flux=2491lm LED Power=17W Eff=51% EfcLed=143lm/W EfcLum=64lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h | | | | | | | |
| C.I.E. | 100 | 100 | 100 | 100 | 100 | D DIN 5040 | A60 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Diam=55mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code AN10720+AP91400
 Name VECTOR 55 TRACK 930 FL DALI BR.BRONZE + ANTI-DAZZLE LOUVRE

Measurerm.


Code FTS1800398-B
 Name VECTOR 55 TRACK 930 FL DALI BR.BRONZE + ANTI-DAZZLE LOUVRE

| | | | | | | | |
|--|---------|-----------------|----------------|-----------------------------|---------------|-----------------|-----------------|
| Luminaire Flux | 1277 lm | Luminaire Power | 20.0 W | Efficacy | 63.850 lm/W | Efficiency | 100.00% |
| Source Flux | 1277 lm | Maximum value | 6688.13 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Round Luminaire | | Diam. | 55 mm | Height | 130 mm | | |
| Round Luminous Area | | Diam. | 48 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.001810 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000438 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 28-02-2024 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1277 lm | |
| LED Flux=2491lm LED Power=17W Eff=51% EfcLed=143lm/W EfcLum=64lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h | | | | | | | |
| C.I.E. | 100 | 100 | 100 | 100 | 100 | D DIN 5040 | A60 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
|------|------|------|------|------|------|------|------|------|------|------|------|
| OA | 0.18 | 0.37 | 0.55 | 0.74 | 0.92 | OC | 0.18 | 0.37 | 0.55 | 0.74 | 0.92 |
| OB | 0.18 | 0.37 | 0.55 | 0.74 | 0.92 | OD | 0.18 | 0.37 | 0.55 | 0.74 | 0.92 |

| | Luminous Intensities [cd/klm] | | | | | | | | | |
|----|---------------------------------|---------|---------|--------|-------|------|------|------|------|------|
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 8540.74 | 7296.46 | 1869.86 | 171.40 | 16.57 | 4.55 | 1.59 | 0.50 | 0.38 | 0.28 |
| OB | 8540.74 | 7296.46 | 1869.86 | 171.40 | 16.57 | 4.55 | 1.59 | 0.50 | 0.38 | 0.28 |
| OC | 8540.74 | 7296.46 | 1869.86 | 171.40 | 16.57 | 4.55 | 1.59 | 0.50 | 0.38 | 0.28 |
| OD | 8540.74 | 7296.46 | 1869.86 | 171.40 | 16.57 | 4.55 | 1.59 | 0.50 | 0.38 | 0.28 |



| H[m] | D[m] | Max lux | Med lux | Alpha=10.4°+10.4° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.37 | 8541 | 5407 | | |
| 2.00 | 0.74 | 2135 | 1352 | | |
| 3.00 | 1.10 | 949 | 601 | | |
| 4.00 | 1.47 | 534 | 338 | | |
| 5.00 | 1.84 | 342 | 216 | | |