


Luminaire

Code AP15201
Name VECTOR 55 MAGNET 940 FL DALI BCO

Measurement

Code FTS1800194
Name VECTOR 55 MAGNET 940 FL DALI BCO

Luminaire Flux	1748 lm	Luminaire Power	23.0 W	Efficacy	76.017 lm/W	Efficiency	100.00%
Source Flux	1748 lm	Maximum value	5833.50 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.000402 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		27-09-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1748 lm	
LED Flux=2383lm LED Power=21W Eff=73% EfcLed=111lm/W EfcLum=76lm/W CCT=4000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	99	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



Luminaire

Code AP15201
Name VECTOR 55 MAGNET 940 FL DALI BCO

Measurerm.


Code FTS1800194
Name VECTOR 55 MAGNET 940 FL DALI BCO

Luminaire Flux	1748 lm	Luminaire Power	23.0 W	Efficacy	76.017 lm/W	Efficiency	100.00%
Source Flux	1748 lm	Maximum value	5833.50 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.000402 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		27-09-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1748 lm	
LED Flux=2383lm LED Power=21W Eff=73% EfcLed=111lm/W EfcLum=76lm/W CCT=4000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.19	0.38	0.58	0.77	0.96	OC	0.19	0.38	0.58	0.77	0.96
OB	0.19	0.38	0.58	0.77	0.96	OD	0.19	0.38	0.58	0.77	0.96

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	10199.24	9039.76	2390.24	566.47	16.39	7.04	4.10	2.77	1.50	0.54
OB	10199.24	9039.76	2390.24	566.47	16.39	7.04	4.10	2.77	1.50	0.54
OC	10199.24	9039.76	2390.24	566.47	16.39	7.04	4.10	2.77	1.50	0.54
OD	10199.24	9039.76	2390.24	566.47	16.39	7.04	4.10	2.77	1.50	0.54



H[m]	D[m]	Max lux	Med lux	Alpha=10.9°+10.9°	G=0.0
1.00	0.38	10199	6547		
2.00	0.77	2550	1637		
3.00	1.15	1133	727		
4.00	1.53	637	409		
5.00	1.92	408	262		