

Luminaire

Code AQ20801+AQ16XXX
 Name A.24 INC. MOD.DIFF.90° PERP 4000K WHT + A.24 SCHERMO DIFF. OPALINO

Measurement

Code FTS1802131-A
 Name A.24 INC. MOD.DIFF.90° PERP 4000K WHT + A.24 SCHERMO DIFF. OPALINO

| | | | | | | | |
|----------------------------|---------|-------------------------|---------------|-----------------------------|-------------------------|-----------------------|-----------------------|
| Luminaire Flux | 1709 lm | Luminaire Power | 14.0 W | Efficacy | 122.071 lm/W | Efficiency | 100.00% |
| Source Flux | 1709 lm | Maximum value | 261.89 cd/klm | Position | C=90.00 G=45.00 | CG | Sym. on planes 270-90 |
| Rectangular Luminaire | | Length | 330 mm | Width | 27 mm | Height | 330 mm |
| Rectangular Luminous Area | | Length | 330 mm | Width | 24 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.007920 m ² | | Emitting area on Plane 180° | 0.000000 m ² | | |
| Emitting area on Plane 0° | | 0.000000 m ² | | Emitting area on Plane 270° | 0.000000 m ² | | |
| Emitting area on Plane 90° | | 0.000000 m ² | | Glare area at 76° | 0.001916 m ² | | |
| Coordinate system | | CG Roads | | Symmetry Type | | Sym. on planes 270-90 | |
| Date | | 20-09-2023 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1709 lm | |

LED Flux=2488lm LED Power=13W Eff=69% EfcLed=187lm/W EfcLum=122lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(17k)=102000h

C.I.E. 36 65 86 77 100

D DIN 5040

B21

