

## Luminaire

Code AQ37301+AQ90XXX  
 Name A.24 PLAF. MOD.DIFF. 90° PERP 2700K WHT + A.24 SCHERMO DIFF. OPALINO FLESSIB.

## Measurement

Code FTS2300217  
 Name A.24 PLAF. MOD.DIFF. 90° PERP 2700K WHT + A.24 SCHERMO DIFF. OPALINO FLESSIB.

|                            |         |                         |               |                             |                 |                         |                       |
|----------------------------|---------|-------------------------|---------------|-----------------------------|-----------------|-------------------------|-----------------------|
| Luminaire Flux             | 1421 lm | Luminaire Power         | 14.0 W        | Efficacy                    | 101.500 lm/W    | Efficiency              | 100.00%               |
| Source Flux                | 1421 lm | Maximum value           | 261.89 cd/klm | Position                    | C=90.00 G=45.00 | CG                      | Sym. on planes 270-90 |
| Rectangular Luminaire      |         | Length                  | 330 mm        | Width                       | 27 mm           | Height                  | 330 mm                |
| Rectangular Luminous Area  |         | Length                  | 330 mm        | Width                       | 24 mm           | Height                  | 0 mm                  |
| Horizontal Luminous Area   |         | 0.007920 m <sup>2</sup> |               | Emitting area on Plane 180° |                 | 0.000000 m <sup>2</sup> |                       |
| Emitting area on Plane 0°  |         | 0.000000 m <sup>2</sup> |               | Emitting area on Plane 270° |                 | 0.000000 m <sup>2</sup> |                       |
| Emitting area on Plane 90° |         | 0.000000 m <sup>2</sup> |               | Glare area at 76°           |                 | 0.001916 m <sup>2</sup> |                       |
| Coordinate system          |         | CG Roads                |               | Symmetry Type               |                 | Sym. on planes 270-90   |                       |
| Date                       |         | 20-09-2023              |               | Maximum Gamma Angle         |                 | 180                     |                       |
| Measurement Distance       |         | 0.00                    |               | Measurement Flux            |                 | 1421 lm                 |                       |

LED Flux=2346lm LED Power=13W Eff=61% EfcLed=176lm/W EfcLum=102lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h

C.I.E. 36 65 86 77 100

D DIN 5040

B21

