

## Luminaire

Code AQ44015  
Name A.24 SOSP.MOD.D.SHARP3000K XF 1176 BSV

## Measurement

Code FTS1802257  
Name A.24 SOSP.MOD.D.SHARP3000K XF 1176 BSV

Luminaire Flux	1731 lm	Luminaire Power	22.0 W	Efficacy	78.668 lm/W	Efficiency	100.00%
Source Flux	1731 lm	Maximum value	1052.56 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1176 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	258 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.003096 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000749 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1731 lm	


LED Flux=2000,1lm LED Power=20W Eff=87% EfcLed=100lm/W EfcLum=79lm/W CCT=3000K Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 98 100 100 100 100  
F UTE --

D DIN 5040  
B NBN

A60  
BZ 1

1176mm x 27mm



Sempiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 0.00 %  
DLOR 100.00 %  
RN 0.00 %

