

Luminaire

Code AQ46401+AQ16XXX
 Name A.24 SOSP. DIR.+IND.DIFF. 2700K 1176 WHT + A.24 SCHERMO DIFF. OPALINO

Measurement

Code FTS1801946-A
 Name A.24 SOSP. DIR.+IND.DIFF. 2700K 1176 WHT + A.24 SCHERMO DIFF. OPALINO

Luminaire Flux	4916 lm	Luminaire Power	43.0 W	Efficacy	114.326 lm/W	Efficiency	100.00%
Source Flux	4916 lm	Maximum value	227.68 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1176 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	1176 mm	Width	22 mm	Height	0 mm
Horizontal Luminous Area		0.025872 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.006259 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4916 lm	


LED Flux=7038lm LED Power=40W Eff=70% EfcLed=176lm/W EfcLum=114lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h

C.I.E. 47 78 95 66 100
 F UTE 0.66 E + 0.34 T

D DIN 5040
 B NBN

B31
 BZ 5

1176mm x 27mm




Semipiani C

180.0 ——— 0.0
 270.0 ——— 90.0

ULOR 34.45 %

DLOR 65.55 %

RN 34.45 %



Luminaire

Code AQ46401+AQ16XXX
 Name A.24 SOSP. DIR.+IND.DIFF. 2700K 1176 WHT + A.24 SCHERMO DIFF. OPALINO

Measurerm.


Code FTS1801946-A
 Name A.24 SOSP. DIR.+IND.DIFF. 2700K 1176 WHT + A.24 SCHERMO DIFF. OPALINO

Luminaire Flux	4916 lm	Luminaire Power	43.0 W	Efficacy	114.326 lm/W	Efficiency	100.00%
Source Flux	4916 lm	Maximum value	227.68 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1176 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	1176 mm	Width	22 mm	Height	0 mm
Horizontal Luminous Area		0.025872 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006259 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4916 lm	
LED Flux=7038lm LED Power=40W Eff=70% EfcLed=176lm/W EfcLum=114lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	47 78 95 66 100			D DIN 5040	B31		
F UTE	0.66 E + 0.34 T			B NBN	BZ 5		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.51	3.01	4.52	6.02	7.53	OC	1.54	3.08	4.62	6.16	7.70
OB	1.51	3.01	4.52	6.02	7.53	OD	1.54	3.08	4.62	6.16	7.70

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1119.29	1114.14	1073.10	995.14	885.59	746.95	582.61	404.28	214.67	52.77
OB	1119.29	1114.14	1073.10	995.14	885.59	746.95	582.61	404.28	214.67	52.77
OC	1119.29	1114.28	1075.31	1000.83	892.01	755.72	595.12	413.40	220.04	58.12
OD	1119.29	1114.28	1075.31	1000.83	892.01	755.72	595.12	413.40	220.04	58.12



H[m]	D[m]	Max lux	Med lux	Alpha=56.4°+56.4°	G=0.0
1.00	3.01	1119	265		
2.00	6.02	280	66		
3.00	9.03	124	29		
4.00	12.04	70	17		
5.00	15.05	45	11		

H[m]	D[m]	Max lux	Med lux	Beta=57.0°+57.0°	G=0.0
1.00	3.08	1119	265		
2.00	6.16	280	66		
3.00	9.24	124	29		
4.00	12.32	70	17		
5.00	15.40	45	11		