

Luminaire


Code AQ46518+AQ16XXX
 Name A.24 SOSP. MODULO DIR.+IND. DIFF. 2700K 2352mm BCOP + A.24 SCHERMO DIFF. OPALINO

Measurement

Code FTS2300166
 Name A.24 SOSP. MODULO DIR.+IND. DIFF. 2700K 2352mm BCOP + A.24 SCHERMO DIFF. OPALINO

Luminaire Flux	8132 lm	Luminaire Power	87.0 W	Efficacy	93.471 lm/W	Efficiency	100.00%
Source Flux	8132 lm	Maximum value	230.58 cd/klm	Position	C=90.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	2352 mm	Width	22 mm	Height	0 mm
Horizontal Luminous Area		0.051744 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.012518 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		8132 lm	
LED Flux=14075lm LED Power=80W Eff=58% EfcLed=176lm/W EfcLum=93lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	47 79 96 66 100			D DIN 5040	B31		
F UTE	0.66 E + 0.34 T			B NBN	BZ 5 / 2 / BZ 4		

2352mm x 27mm




Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 34.08 %

DLOR 65.92 %

RN 34.08 %



Luminaire

Code AQ46518+AQ16XXX
 Name A.24 SOSP. MODULO DIR.+IND. DIFF. 2700K 2352mm BCOP + A.24 SCHERMO DIFF. OPALINO

Measurement


Code FTS2300166
 Name A.24 SOSP. MODULO DIR.+IND. DIFF. 2700K 2352mm BCOP + A.24 SCHERMO DIFF. OPALINO

Luminaire Flux	8132 lm	Luminaire Power	87.0 W	Efficacy	93.471 lm/W	Efficiency	100.00%
Source Flux	8132 lm	Maximum value	230.58 cd/klm	Position	C=90.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	2352 mm	Width	22 mm	Height	0 mm
Horizontal Luminous Area	0.051744 m2			Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°			0.012518 m2
Coordinate system	CG			Symmetry Type			Double Symmetrical
Date	20-09-2023			Maximum Gamma Angle			180
Measurement Distance	0.00			Measurement Flux			8132 lm
LED Flux=14075lm LED Power=80W Eff=58% EfcLed=176lm/W EfcLum=93lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(17k)=102000h							
C.I.E.	47 79 96 66 100			D DIN 5040	B31		
F UTE	0.66 E + 0.34 T			B NBN	BZ 5 / 2 / BZ 4		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.48	2.97	4.45	5.94	7.42	OC	1.54	3.07	4.61	6.15	7.69
OB	1.48	2.97	4.45	5.94	7.42	OD	1.54	3.07	4.61	6.15	7.69

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1875.06	1865.75	1794.54	1662.23	1475.77	1240.14	967.76	661.36	346.20	76.19
OB	1875.06	1865.75	1794.54	1662.23	1475.77	1240.14	967.76	661.36	346.20	76.19
OC	1875.06	1866.86	1802.16	1674.31	1494.25	1264.29	992.99	690.61	369.40	96.94
OD	1875.06	1866.86	1802.16	1674.31	1494.25	1264.29	992.99	690.61	369.40	96.94



H[m]	D[m]	Max lux	Med lux	Alpha=56.0°+56.0°	G=0.0
1.00	2.97	1875	448		
2.00	5.94	469	112		
3.00	8.90	208	50		
4.00	11.87	117	28		
5.00	14.84	75	18		

H[m]	D[m]	Max lux	Med lux	Beta=57.0°+57.0°	G=0.0
1.00	3.07	1875	448		
2.00	6.15	469	112		
3.00	9.22	208	50		
4.00	12.30	117	28		
5.00	15.37	75	18		