

Luminaire

Code AQ47201
Name A.24 SOSP. MODULO DIR.+IND. SHARP 3000K FL 2352mm WHT

Measurement

Code FTS1802337-B
Name A.24 SOSP. MODULO DIR.+IND. SHARP 3000K FL 2352mm WHT

Luminaire Flux	6848 lm	Luminaire Power	74.0 W	Efficacy	92.541 lm/W	Efficiency	100.00%
Source Flux	6848 lm	Maximum value	1338.32 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2352 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	516 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.006192 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.001498 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6848 lm	
LED Flux=8976lm LED Power=65W Eff=76% EfcLed=139lm/W EfcLum=93lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=102000h							
C.I.E.	98 100 100 48 100			D DIN 5040		C62	
F UTE	--			B NBN		BZ 1	



