

Luminaire


Code AQ47820
Name A.24 SOSP.MOD.D+IN SHARP3000K XF 1176 BBRZ

Measurement

Code FTS2300244
Name A.24 SOSP.MOD.D+IN SHARP3000K XF 1176 BBRZ

Luminaire Flux	3200 lm	Luminaire Power	36.0 W	Efficacy	88.889 lm/W	Efficiency	100.00%
Source Flux	3200 lm	Maximum value	569.23 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1176 mm	Width	27 mm	Height	55 mm
Rectangular Luminous Area		Length	258 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.003096 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.000749 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3200 lm	
LED Flux=4488lm LED Power=33W Eff=71% EfcLed=135lm/W EfcLum=89lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=102000h							
C.I.E.	98 100 100 54 100			D DIN 5040		C61	
F UTE	--			B NBN		BZ 1	

1176mm x 27mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 45.91 %

DLOR 54.09 %

RN 45.91 %

