

Luminaire

Code AQ60415
Name A.24 PLAF CURVA 60 R561 SHRP XF3000K BSV

Measurement

Code FTS1902270-A
Name A.24 PLAF CURVA 60 R561 SHRP XF3000K BSV

Luminaire Flux	865 lm	Luminaire Power	11.0 W	Efficacy	78.664 lm/W	Efficiency	100.00%
Source Flux	865 lm	Maximum value	1052.56 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	587 mm	Width	24 mm	Height	55 mm
Rectangular Luminous Area		Length	129 mm	Width	12 mm	Height	0 mm
Horizontal Luminous Area		0.001548 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000374 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		01-08-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		865 lm	
LED Flux=1000lm LED Power=10W Eff=87% EfcLed=100lm/W EfcLum=79lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(6K)=118000h							
C.I.E.	98 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		



