

Luminaire

Code BB00300+DV1018
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W DIM

Measurem.

Code FTS1801175
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W DIM

Luminaire Flux	2537.80 lm	Luminaire Power	27.00 W	Efficacy	93.99 lm/W	Efficiency	100.00%
Sources Flux	2537.80 lm	Maximum value	738.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	211 mm	Height	177 mm		
Round Luminous Area		Diam.	200 mm	Height	0 mm		
Horizontal Luminous Area			0.031416 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.007600 m2
Coordinate system		CG		Symmetry Type			Rotosymmetrical
Date		15-06-2018		Maximum Gamma Angle			180
Measurement Distance		0.00		Measurement Flux			2537.80 lm
LED Flux=3130lm LED Power=25W Eff=81% EfcLed=125lm/W EfcLum=94lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	77 92 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1 / 1.5 / BZ 2		


Diam=211mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code BB00300+DV1018
Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W DIM

Measurerm.

Code FTS1801175
Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W DIM


Luminaire Flux	2537.80 lm	Luminaire Power	27.00 W	Efficacy	93.99 lm/W	Efficiency	100.00%
Sources Flux	2537.80 lm	Maximum value	738.97 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	211 mm	Height	177 mm		
Round Luminous Area		Diam.	200 mm	Height	0 mm		
Horizontal Luminous Area		0.031416 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.007600 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		15-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2537.80 lm	
LED Flux=3130lm LED Power=25W Eff=81% EfcLed=125lm/W EfcLum=94lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	77 92 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1 / 1.5 / BZ 2		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.69	1.38	2.07	2.77	3.46	OC	0.69	1.38	2.07	2.77	3.46
OB	0.69	1.38	2.07	2.77	3.46	OD	0.69	1.38	2.07	2.77	3.46

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	1875.35	1850.27	1706.40	1486.56	908.29	354.55	177.45	129.43	54.00	7.24
OB	1875.35	1850.27	1706.40	1486.56	908.29	354.55	177.45	129.43	54.00	7.24
OC	1875.35	1850.27	1706.40	1486.56	908.29	354.55	177.45	129.43	54.00	7.24
OD	1875.35	1850.27	1706.40	1486.56	908.29	354.55	177.45	129.43	54.00	7.24



H[m]	D[m]	Max lux	Med lux	Alpha=34.7°+34.7°	G=0.0
1.00	1.38	1875	923		
2.00	2.77	469	231		
3.00	4.15	208	103		
4.00	5.53	117	58		
5.00	6.91	75	37		