

## Luminaire

Code BB00300+DV1018 + M239600  
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W DIM + schermo prismoptico

## Measurement

Code FTS1801367  
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W DIM + schermo prismoptico

Luminaire Flux	2106.18 lm	Luminaire Power	27.00 W	Efficacy	78.01 lm/W	Efficiency	100.00%
Sources Flux	2106.18 lm	Maximum value	701.79 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	336 mm	Height	260 mm		
Round Luminous Area		Diam.	196 mm	Height	0 mm		
Horizontal Luminous Area			0.030172 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.007299 m2
Coordinate system		CG		Symmetry Type			Rotosymmetrical
Date		21-06-2018		Maximum Gamma Angle			180
Measurement Distance		0.00		Measurement Flux			2106.18 lm
LED Flux=3130lm LED Power=25W Eff=67% EfcLed=125lm/W EfcLum=78lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	72 93 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 2		


Diam=336mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
 DLOR100.00 %  
 RN 0.00 %



## Luminaire

Code BB00300+DV1018 + M239600  
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W DIM + schermo prismoptico

## Measurement


Code FTS1801367  
 Name LUCERI TLESS ROUND.max46W 930 COMFORT + Driver 35W DIM + schermo prismoptico

Luminaire Flux	2106.18 lm	Luminaire Power	27.00 W	Efficacy	78.01 lm/W	Efficiency	100.00%
Sources Flux	2106.18 lm	Maximum value	701.79 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	336 mm	Height	260 mm		
Round Luminous Area		Diam.	196 mm	Height	0 mm		
Horizontal Luminous Area		0.030172 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		21-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2106.18 lm	
LED Flux=3130lm LED Power=25W Eff=67% EfcLed=125lm/W EfcLum=78lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	72 93 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 2		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.70	1.40	2.09	2.79	3.49	OC	0.70	1.40	2.09	2.79	3.49
OB	0.70	1.40	2.09	2.79	3.49	OD	0.70	1.40	2.09	2.79	3.49

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	1478.10	1465.95	1345.89	1074.86	736.33	397.92	194.91	100.42	41.74	6.04
OB	1478.10	1465.95	1345.89	1074.86	736.33	397.92	194.91	100.42	41.74	6.04
OC	1478.10	1465.95	1345.89	1074.86	736.33	397.92	194.91	100.42	41.74	6.04
OD	1478.10	1465.95	1345.89	1074.86	736.33	397.92	194.91	100.42	41.74	6.04



H[m]	D[m]	Max lux	Med lux	Alpha=34.9°+34.9°	G=0.0
1.00	1.40	1478	697		
2.00	2.79	370	174		
3.00	4.19	164	77		
4.00	5.59	92	44		
5.00	6.98	59	28		