


Luminaire

Code BB10400+DV1018 + M239200
 Name LUCERI Q TLESS ROUND.max 46W 940 COMFORT + Driver 35W DIM + schermo trasparente


Measurement

Code FTS1801244
 Name LUCERI Q TLESS ROUND.max 46W 940 COMFORT + Driver 35W DIM + schermo trasparente

Luminaire Flux	2224.08 lm	Luminaire Power	27.00 W	Efficacy	82.37 lm/W	Efficiency	100.00%
Sources Flux	2224.08 lm	Maximum value	855.25 cd/klm	Position	C=10.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire Rectangular Luminous Area	Length Length	318 mm 170 mm	Width Width	318 mm 170 mm	Height Height	280 mm 0 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.028900 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.006992 m2			
Coordinate system Date Measurement Distance	CG 20-06-2018 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux	Double Symmetrical 180 2224.08 lm			
LED Flux=3348lm LED Power=25W Eff=66% EfcLed=134lm/W EfcLum=82lm/W CCT=4000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E. F UTE	79 94 99 100 100 1.00 B		D DIN 5040 B NBN	A60 BZ 1			



ULOR 0.03 %
 DLOR 99.97 %
 RN 0.03 %



Luminaire

Code BB10400+DV1018 + M239200
 Name LUCERI Q TLESS ROUND.max 46W 940 COMFORT + Driver 35W DIM + schermo trasparente

Measurement

Code FTS1801244
 Name LUCERI Q TLESS ROUND.max 46W 940 COMFORT + Driver 35W DIM + schermo trasparente

Luminaire Flux	2224.08 lm	Luminaire Power	27.00 W	Efficacy	82.37 lm/W	Efficiency	100.00%
Sources Flux	2224.08 lm	Maximum value	855.25 cd/klm	Position	C=10.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	318 mm	Width	318 mm	Height	280 mm
Rectangular Luminous Area		Length	170 mm	Width	170 mm	Height	0 mm
Horizontal Luminous Area		0.028900 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006992 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2224.08 lm	


LED Flux=3348lm LED Power=25W Eff=66% EfcLed=134lm/W EfcLum=82lm/W CCT=4000K Ra=90 SDCM=1 L70(6K)=50000h

C.I.E.	79 94 99 100 100	D DIN 5040	A60
F UTE	1.00 B	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.57	1.14	1.71	2.29	2.86	OC	0.57	1.14	1.72	2.29	2.86
OB	0.57	1.14	1.71	2.29	2.86	OD	0.57	1.14	1.72	2.29	2.86

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1901.47	1891.75	1703.54	1314.99	583.39	234.63	147.29	88.86	32.98	7.39
OB	1901.47	1891.75	1703.54	1314.99	583.39	234.63	147.29	88.86	32.98	7.39
OC	1901.47	1885.72	1701.97	1318.88	587.36	232.54	148.01	88.61	32.21	7.04
OD	1901.47	1885.72	1701.97	1318.88	587.36	232.54	148.01	88.61	32.21	7.04



H[m]	D[m]	Max lux	Med lux	Alpha=29.8°+29.8°	G=0.0° Max non a G
1.00	1.14	1902	1077		
2.00	2.29	475	269		
3.00	3.43	211	120		
4.00	4.57	119	67		
5.00	5.72	76	43		

H[m]	D[m]	Max lux	Med lux	Beta=29.8°+29.8°	G=0.0° Max non a G
1.00	1.14	1902	1077		
2.00	2.29	475	269		
3.00	3.43	211	120		
4.00	4.58	119	67		
5.00	5.72	76	43		