


Luminaire

Code BB11000+DV1016 + M239600
 Name LUCERI Q TLESS CUT.EDGEmax46W 930 MIRROR + Driver 50W DIM + schermo prismoptic

Measurement

Code FTS1801341
 Name LUCERI Q TLESS CUT.EDGEmax46W 930 MIRROR + Driver 50W DIM + schermo prismoptic

Luminaire Flux	3725.21 lm	Luminaire Power	54.00 W	Efficacy	68.99 lm/W	Efficiency	100.00%
Sources Flux	3725.21 lm	Maximum value	974.90 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	236 mm	Width	236 mm	Height	185 mm
Rectangular Luminous Area		Length	170 mm	Width	170 mm	Height	0 mm
Horizontal Luminous Area		0.028900 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006992 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3725.21 lm	
LED Flux=5451lm LED Power=50W Eff=68% EfcLed=109lm/W EfcLum=69lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	81 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1		



ULOR 0.01 %
 DLOR 99.99 %
 RN 0.01 %

