

## Luminaire

Code BB12005+DV1016 + M239600  
 Name LUCERI Q TRIM max46W 930 MIRROR SILV. + Driver 50W DIM + schermo prismoptic

## Measurem.

Code FTS1801341  
 Name LUCERI Q TRIM max46W 930 MIRROR SILV. + Driver 50W DIM + schermo prismoptic


Luminaire Flux	3725.21 lm	Luminaire Power	54.00 W	Efficacy	68.99 lm/W	Efficiency	100.00%
Sources Flux	3725.21 lm	Maximum value	974.90 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	236 mm	Width	236 mm	Height	185 mm
Rectangular Luminous Area		Length	170 mm	Width	170 mm	Height	0 mm
Horizontal Luminous Area		0.028900 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006992 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3725.21 lm	

LED Flux=5451lm LED Power=50W Eff=68% EfcLed=109lm/W EfcLum=69lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h


C.I.E. 81 97 99 100 100  
 F UTE 1.00 B

D DIN 5040  
 B NBN

A60  
 BZ 1



ULOR 0.01 %  
 DLOR 99.99 %  
 RN 0.01 %



## Luminaire

Code BB12005+DV1016 + M239600  
 Name LUCERI Q TRIM max46W 930 MIRROR SILV. + Driver 50W DIM + schermo prismoptico

## Measurement


Code FTS1801341  
 Name LUCERI Q TRIM max46W 930 MIRROR SILV. + Driver 50W DIM + schermo prismoptico

Luminaire Flux	3725.21 lm	Luminaire Power	54.00 W	Efficacy	68.99 lm/W	Efficiency	100.00%
Sources Flux	3725.21 lm	Maximum value	974.90 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	236 mm	Width	236 mm	Height	185 mm
Rectangular Luminous Area		Length	170 mm	Width	170 mm	Height	0 mm
Horizontal Luminous Area		0.028900 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.006992 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-06-2018		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3725.21 lm	
LED Flux=5451lm LED Power=50W Eff=68% EfcLed=109lm/W EfcLum=69lm/W CCT=3000K Ra=90 SDCM=1 L70(6K)=50000h							
C.I.E.	81 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.54	1.08	1.62	2.16	2.70	OC	0.54	1.09	1.63	2.18	2.72
OB	0.54	1.08	1.62	2.16	2.70	OD	0.54	1.09	1.63	2.18	2.72

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	3631.72	3575.79	3057.90	2132.16	1236.60	566.25	219.40	83.35	29.96	7.91
OB	3631.72	3575.79	3057.90	2132.16	1236.60	566.25	219.40	83.35	29.96	7.91
OC	3631.72	3585.47	3060.01	2138.41	1281.14	605.33	234.51	89.20	31.94	7.80
OD	3631.72	3585.47	3060.01	2138.41	1281.14	605.33	234.51	89.20	31.94	7.80



H[m]	D[m]	Max lux	Med lux	Alpha=28.3°+28.3°	G=0.0
1.00	1.08	3632	1903		
2.00	2.16	908	476		
3.00	3.24	404	211		
4.00	4.31	227	119		
5.00	5.39	145	76		

H[m]	D[m]	Max lux	Med lux	Beta=28.5°+28.5°	G=0.0
1.00	1.09	3632	1903		
2.00	2.18	908	476		
3.00	3.26	404	211		
4.00	4.35	227	119		
5.00	5.44	145	76		