

Luminaire

Code BB12305_N+M239500
 Name LUCERI Q TRIM 36W 230V TW MIRROR SILV.LUCERI KADRO DIFFUSORE PRISMOPTIC

Measurement


Code FTS2102277
 Name LUCERI Q TRIM 36W 230V TW MIRROR SILV.LUCERI KADRO DIFFUSORE PRISMOPTIC

Luminaire Flux	2462.26 lm	Luminaire Power	36.00 W	Efficacy	68.40 lm/W	Efficiency	100.00%
Sources Flux	2462.26 lm	Maximum value	1016.15 cd/klm	Position	C=0.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	318 mm	Width	318 mm	Height	195 mm
Rectangular Luminous Area		Length	173 mm	Width	173 mm	Height	0 mm
Horizontal Luminous Area		0.029929 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007240 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		30-06-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2462.26 lm	


LED Flux=3725lm LED Power=32W Eff=66% EfcLed=117lm/W EfcLum=68lm/W CCT=6000K Ra=90 SDCM=3 L70(10K)=55000

C.I.E. 83 96 99 100 100
 F UTE 1.00 B

D DIN 5040
 B NBN
 A60
 BZ 1



ULOR 0.01 %
 DLOR 99.99 %
 RN 0.01 %



Luminaire

Code BB12305_N+M239500
 Name LUCERI Q TRIM 36W 230V TW MIRROR SILV.LUCERI KADRO DIFFUSORE PRISMOPTIC

Measurment


Code FTS2102277
 Name LUCERI Q TRIM 36W 230V TW MIRROR SILV.LUCERI KADRO DIFFUSORE PRISMOPTIC

Luminaire Flux	2462.26 lm	Luminaire Power	36.00 W	Efficacy	68.40 lm/W	Efficiency	100.00%
Sources Flux	2462.26 lm	Maximum value	1016.15 cd/klm	Position	C=0.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	318 mm	Width	318 mm	Height	195 mm
Rectangular Luminous Area		Length	173 mm	Width	173 mm	Height	0 mm
Horizontal Luminous Area		0.029929 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007240 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		30-06-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2462.26 lm	
LED Flux=3725lm LED Power=32W Eff=66% EfcLed=117lm/W EfcLum=68lm/W CCT=6000K Ra=90 SDCM=3 L70(10K)=55000							
C.I.E.	83 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.52	1.04	1.56	2.08	2.60	OC	0.52	1.04	1.55	2.07	2.59
OB	0.52	1.04	1.56	2.08	2.60	OD	0.52	1.04	1.55	2.07	2.59

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2501.74	2472.82	2148.82	1444.97	718.02	293.89	124.53	54.35	24.50	4.94
OB	2501.74	2472.82	2148.82	1444.97	718.02	293.89	124.53	54.35	24.50	4.94
OC	2501.74	2469.07	2140.46	1438.18	725.06	317.13	137.12	61.60	26.89	5.33
OD	2501.74	2469.07	2140.46	1438.18	725.06	317.13	137.12	61.60	26.89	5.33



H[m]	D[m]	Max lux	Med lux	Alpha=27.5°+27.5°	G=0.0 Max non a G
1.00	1.04	2502	1390		
2.00	2.08	625	347		
3.00	3.12	278	154		
4.00	4.16	156	87		
5.00	5.20	100	56		

H[m]	D[m]	Max lux	Med lux	Beta=27.4°+27.4°	G=0.0 Max non a G
1.00	1.04	2502	1390		
2.00	2.07	625	347		
3.00	3.11	278	154		
4.00	4.14	156	87		
5.00	5.18	100	56		