

Luminaire

Code BH08501+BH16101
 Name A.39 SHARP D+IND 1184 HB 34 400K ND BCO + COVER 3X4 OPT. HB WHITE

Measurerm.

Code FTS1900421
 Name A.39 SHARP D+IND 1184 HB 34 400K ND BCO + COVER 3X4 OPT. HB WHITE

Luminaire Flux	5564.43 lm	Luminaire Power	64.00 W	Efficacy	86.94 lm/W	Efficiency	100.00%
Sources Flux	5564.43 lm	Maximum value	1143.88 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	444 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.016428 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003974 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5564.43 lm	
LED Flux=7122,45lm LED Power=55W Eff=78% EfcLed=129lm/W EfcLum=87lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97 99 100 44 100			D DIN 5040	C62		
F UTE	--			B NBN	BZ 1		

1184mm x 40mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 55.50 %
 DLOR 44.50 %
 RN 55.50 %



